Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-752-7044

Section Quantity:

1

- Body Style:
- Rectangular w/bushing
- **Reliability Indicator:**
- Not established
- **Overall Length:**
- 1.562 inches
- **Overall Height:**
- 0.406 inches
- **Overall Width:**
- 0.266 inches
- Shaft Diameter:
- 0.115 inches
- Shaft Length:
- 0.250 inches
- Mounting Bushing Length:
- 0.250 inches
- **Body Length:**
- 1.312 inches
- Body Width:
- 0.266 inches
- Body Height:
- 0.406 inches
- Shaft Style:
- Round, slotted
- Actuator Type:
- Single shaft
- Screw Thread Diameter:
- 0.190 inches
- Screw Thread Series Designator:
- Unf
- Screw Thready Qty Per Inch (tpi):
- 32.0
- Terminal Location:
- Rear end
- Mounting Method:
- Standard bushing
- **Electrical Resistance Per Section:**
- 10.000 kilohms single section
- **Rotary Actuator Travel In Angular Deg:**
- 7920.0



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire loop Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0