NSN 5905-00-752-7484

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-752-7484

Section Quantity: 1 Body Style: Cylindrical tab/flange mounted Reliability Indicator: Not established Overall Length: 0.375 inches Body Diameter: Between 0.769 inches and 0.801 inches
Body Style: Cylindrical tab/flange mounted Reliability Indicator: Not established Overall Length: 0.375 inches Body Diameter:
Cylindrical tab/flange mounted Reliability Indicator: Not established Overall Length: 0.375 inches Body Diameter:
Reliability Indicator: Not established Overall Length: 0.375 inches Body Diameter:
Not established Overall Length: 0.375 inches Body Diameter:
Overall Length: 0.375 inches Body Diameter:
0.375 inches Body Diameter:
Body Diameter:
•
Between 0.769 inches and 0.801 inches
Mounting Hole Diameter:
0.136 inches
Body Length:
0.375 inches
Overall Diameter:
1.250 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
240.0
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Unthreaded hole
Features Provided:
Grounded contact arm
Electrical Resistance Per Section:
500.000 ohms single section
Rotary Actuator Travel In Angular Deg:
240.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Continuous motion

NSN 5905-00-752-7484

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power
55.0 single section
Standard Taper Curve Per Section:
A single section

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0