NSN 5905-00-754-5749

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-754-5749 **Section Quantity: Reliability Indicator:** Not established First Flat Length: 0.344 inches Flat Height: 0.185 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.375 inches **Shaft Style:** Round, parallel flatted **Actuator Type:** Single shaft **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 100.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Standard Taper Curve Per Section:** A single section

A single section

Terminal Type And Quantity:
3 tab, solder lug

Shelf Life:
N/a

Unit Of Measure:

--

NSN 5905-00-754-5749

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



em			

No

Fiig:

A002a0