## NSN 5905-00-754-8744

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-754-8744 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.050 inches **Terminal Length:** 6.000 inches **Overall Height:** 0.315 inches **Overall Width:** 0.170 inches **Mounting Hole Diameter:** 0.094 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.050 inches **Body Length:** 1.000 inches **Body Width:** 0.170 inches **Body Height:** 0.315 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation: Lateral Distance Between Mounting Hole Centers:** 0.750 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** 

Unthreaded hole

**Electrical Resistance Per Section:** 

1.000 kilohms single section

## NSN 5905-00-754-8744

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## **Rotary Actuator Travel In Angular Deg:** 5400.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -70.0 to 70.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:** Demilitarization: No