NSN 5905-00-754-8745

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-754-8745 **Section Quantity:** 2 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established liilength: 1.312 inches liiheight: 0.312 inches liiwidth: 0.500 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.062 inches **Body Length:** 1.250 inches **Body Width:** 0.500 inches **Body Height:** 0.312 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:**

2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 10.000 kilohms all sections **Rotary Actuator Travel In Angular Deg:** 9000.0

NSN 5905-00-754-8745

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 135.0 all sections **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0 to 50.0 all sections **Power Dissipation Rating Per Section In Watts:** 0.50 free air all sections **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 all sections **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections **Terminal Type And Quantity:** 6 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:**