

View Online at <https://aerobasegroup.com/nsn/5905-00-755-0828>

**Section Quantity:**

5

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 0.4950 inches and 0.5050 inches

**Pilot Length:**

0.1250 inches

**Overall Length:**

5.344 inches

**Undercut Diameter:**

1.750 inches

**Undercut Width:**

0.0730 inches

**Body Diameter:**

1.755 inches

**Angle Of Mounting Hole In Deg:**

90.0

**Angle Between Centerlines Of Mounting Holes In Deg:**

120.0

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

Between 0.109 inches and 0.141 inches

**Body Length:**

4.219 inches

**Overall Diameter:**

2.002 inches

**Mounting Lip Diameter:**

2.0620 inches

**Mounting Lip Depth:**

0.0930 inches

**Mounting Hole/stud Circle Diameter:**

Between 0.870 inches and 0.880 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Ball

**Switch Type:**

Rotary

**Switch Voltage Rating In Volts:**

35.0 and 250.0 and 250.0

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

350.0

**Maximum Starting Torque:**

6.50 inch-ounces

**Maximum Running Torque:**

4.00 inch-ounces

**Shaft Runout:**

0.001 inches

**Switch Operating Position:**

Start of linear movement

**Switch Contact Arrangement:**

Single pole, single throw, normally open, both positions maintained

**Screw Thread Diameter:**

0.138 inches

**Screw Thread Series Designator:**

Unc

**Screw Thread Qty Per Inch (tpi):**

32.0

**Mounting Facility Quantity:**

4

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Threaded hole

**Features Provided:**

Switch

**Electrical Resistance Per Section:**

80.000 percent, rated amperes c and better select

**Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:**

175.0 all sections

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.30/+0.30 all sections

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 all sections

**Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

**Function Conformity Per Section:**

All sections terminal base linearity

**Fixed Tap Quantity Per Section:**

1 5th section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 all sections

**Actuator Travel Control Feature:**

Continuous motion

**Tap Location From Ccw Terminal Per Section In Ohms:**

40000.0 3rd section

**Function Characteristic Per Section:**

All sections linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 all sections

**Switch Current Type And Rating In Amps:**

0.500 dc and 0.001 dc and 0.010 dc

**Special Features:**

3 switch sections

**Terminal Type And Quantity:**

26 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0