

View Online at <https://aerobasegroup.com/nsn/5905-00-755-0850>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.562 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.219 inches

Mounting Bushing Length:

0.375 inches

Body Length:

3.500 inches

Undercut Diameter:

Between 0.186 inches and 0.189 inches

Shaft Style:

Round, stepped

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Fragility Factor:

Moderately rugged

Undercut Length:

0.344 inches

Screw Thread Diameter:

0.375 inches and 0.164 inches

Screw Thread Series Designator:

Unef and unc

Screw Thread Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

4

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing and threaded hole

Features Provided:

Humidity proof

Electrical Resistance Per Section:

100.0 ohms 1st section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 all sections

Power Dissipation Rating Per Section In Watts:

25.0 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0