NSN 5905-00-755-2212

Section Quantity:

Reliability Indicator:

Not established

Overall Length:

1.375 inches

Terminal Length:

Rectangular w/mounting holes/slots

Body Style:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-755-2212

11.500 inches
Overall Height:
Between 0.300 inches and 0.320 inches
Overall Width:
Between 0.180 inches and 0.200 inches
Mounting Hole Diameter:
0.086 inches
Shaft Diameter:
Between 0.100 inches and 0.120 inches
Shaft Length:
Between 0.060 inches and 0.080 inches
Body Length:
Between 1.240 inches and 1.260 inches
Body Width:
Between 0.180 inches and 0.200 inches
Body Height:
Between 0.300 inches and 0.320 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Lateral Distance Between Mounting Hole Centers:
Between 0.990 inches and 1.010 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
10.000 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section

NSN 5905-00-755-2212

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watt	s:
--	----

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0