NSN 5905-00-755-2446

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-755-2446

Section Quantity: 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 0.344 inches and 0.406 inches **Terminal Length:** Between 0.313 inches and 0.375 inches **Body Diameter:** Between 0.719 inches and 0.781 inches **Body Length:** Between 0.344 inches and 0.406 inches **Overall Diameter:** Between 1.219 inches and 1.281 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 240.0 **Mounting Facility Quantity:** 2 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Flange **Features Provided:** Grounded contact arm **Electrical Resistance Per Section:** 5.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 240.0 **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:**

A single section

NSN 5905-00-755-2446

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
1 tab, solder lug
Shelf Life:
N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0