Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-755-2446

Section Quantity:

1

Body Style: Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 0.344 inches and 0.406 inches **Terminal Length:** Between 0.313 inches and 0.375 inches **Body Diameter:** Between 0.719 inches and 0.781 inches **Body Length:** Between 0.344 inches and 0.406 inches **Overall Diameter:** Between 1.219 inches and 1.281 inches Actuator Type: Flush drive with slot-hole Effective Electrical Rotation In Deg Angular Rotation: 240.0 **Mounting Facility Quantity:** 2 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Flange **Features Provided:** Grounded contact arm

Electrical Resistance Per Section:

5.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

240.0

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:

1 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0