NSN 5905-00-755-2769

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-755-2769 **Section Quantity: Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.375 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.878 inches **Mounting Bushing Length:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.500 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity: Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 8.000 ohms single section **Power Dissipation Rating Per Section In Watts: Resistance Tolerance Per Section In Percent:**

50.0 free air single section -10.0 to 10.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life:

N/a

NSN 5905-00-755-2769

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0