## NSN 5905-00-755-5490

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-755-5490 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.5620 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 1.625 inches **Undercut Width:** 0.0720 inches **Body Diameter:** 1.750 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 1.000 inches **Body Length:** 0.802 inches **Mounting Lip Diameter:** 1.7500 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 40.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Electrical Resistance Per Section:** 10.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 360.0

## **Function Conformity Tolerance Per Section:**

-1.00/+1.00 single section

## NSN 5905-00-755-5490

Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 155.0 single section **Power Dissipation Rating Per Section In Watts:** 4.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Continuous motion **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Terminal Type And Quantity:** 3 turret Shelf Life: N/a **Unit Of Measure: Demilitarization:** No