## NSN 5905-00-755-7875

**Fiig:** A001a0

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-755-7875

-400.0/+400.0 Electrical Resistance: 2.000 ohms Resistance Tolerance in Percent: 5.0004-5.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Eul Rated Power: 35.0 Ambient Tempurature in Deg Celsius At Eul Rated Power: 35.0 Ambient Tempurature Range of Tempurature Coefficient in Deg Celsius: 55.04-350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Resiabilish Indicator: Not established Terminal Length: 0.888 inches Body Diameter: 1.320 inches Power Dissipation Rating in Watts: 210.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.) Specification Data: 81349-mil-26/3 powernment specification Sheff Life: Na Unit Of Measure: — Demilitarization:	Towns we true Coefficient Of Desigtance In Daw Des Coloine
Electrical Resistance: 2.000 ohms Resistance Tolerance in Percent: -5.000/45.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/45.00 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/45.00 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.688 inches Body Diamete: 1.312 inches Body Length: 1.0500 inches Power Dissipation Rating in Watts: 210.000 free air Terminal Width: 0.328 inches Sylo Designator: Rediability and Width: 0.328 inches Sylo Designator: Rediability and Syspedication (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 184349-mill-24230 government specification Shelf Life: Na Unit of Measure: - Demilitarization:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
2.000 ohms Resistance Tolerance In Percent: -5.000/45.000 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.04.95.0 Inclosure Method: Encapsulated Terminal Type:	
Resistance Tolerance in Percent: 5.00045.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 35.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 5.5.04.95.0.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.688 inches Body Diameter: 1.312 inches Body Langth: 10.500 inches Power Dissipation Rating in Watts: 21.0.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-26/3 specification (includes engineering type builletins, brochures, etc., that reflect specification type data in specification forma excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-26/3 by overnment specification Shelf Life: Na Unit of Measure: — Demilitarization:	
-5.00045.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 36.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-350.0 Inclosure Method: Encapsulated Terminal Type: Tab. solder lug Reliability Indicator: Note established Terminal Length: 0.688 inches Body Diameter: 1.1312 inches Body Langth: 10.500 inches Power Dissipation Rating In Watts: 210.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-26/3b government specification Shelf Life: Na Unit Of Measure: Demilitarization:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/4350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.688 inches Body Diameter: 1.312 inches Body Length: 10.500 inches Power Dissipation Rating In Watts: 210.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil+-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 8149-mil+-26/3b government specification Shelf Life: Na Unit Of Measure:	
25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.688 inches Body Diameter: 1.312 inches Body Length: 10.500 inches Power Dissipation Rating In Watts: 210.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil+-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil+-26/3b government specification Shelf Life: No Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated  Terminal Type: Tab. solder lug Reliability Indicator: Not established  Terminal Length: 0.688 inches  Body Diameter: 1.312 inches Body Jength: 10.500 inches  Power Dissipation Rating In Watts: 210.000 free air  Terminal Width: 0.328 inches  Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  Specification Data: 81349-mil-r-26/3b government specification Shelf Life: Via Unit Of Measure:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.688 inches Body Diameter: 1.312 inches Body Diameter: 1.312 inches Body Diameter: 1.312 inches Power Dissipation Rating In Watts: 210.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-26/3b government specification Shef Life: Via Unit Of Measure:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.688 inches Body Diameter: 1.312 inches Body Diameter: 1.312 inches Body Length: 10.500 inches Power Dissipation Rating In Watts: 210.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-26/3b government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
-5.0/+35.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.688 inches Body Diameter: 1.312 inches Body Length: 10.500 inches Power Dissipation Rating In Watts: 210.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-26/3b government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Longth: 0.688 inches Body Diameter: 1.312 inches Body Length: 1.350 inches Power Dissipation Rating In Watts: 210.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mili-726/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formar excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mili-7-26/3b government specification Sheft Life: Na Unit Of Measure: Demilitarization:	
Encapsulated Torminal Type: Tab, solder lug Reliability Indicator: Not established Torminal Length: 0.688 inches Body Diameter: 1.312 inches Body Length: 10.500 inches Power Dissipation Rating In Watts: 210.000 free air Torminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mill-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Date: Shelf Life: N/a Unit Of Measure: Demilitarization:	-55.0/+350.0
Terminal Type: Tab, solder lug  Reliability Indicator: Not established  Terminal Length: 0.688 inches  Body Diameter: 1.312 inches  Body Length: 10.500 inches  Power Dissipation Rating in Watts: 210.000 free air  Terminal Width: 0.328 inches  Style Designator: Radial terminal each end  Test Data Document: 81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-26/3b government specification  Shelf Life: Na  Unit Of Measure: Demilitarization:	Inclosure Method:
Tab. solder lug  Reliability Indicator: Not established  Terminal Length: 0.688 inches  Body Diameter: 1.312 inches  Body Length: 10.500 inches  Power Dissipation Rating In Watts: 210.000 free air  Terminal Width: 0.328 inches  Style Designator: Radial terminal each end  Test Data Document: 81349-mill-r-26/3s pecification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-26/3b government specification  Shelf Life: N/a  Unit Of Measure: Demilitarization:	Encapsulated
Reliability Indicator: Not established  Terminal Length: 0.688 Inches  Body Diameter: 1.312 Inches  Body Length: 10.500 Inches  Power Dissipation Rating In Watts: 210.000 free air  Terminal Width: 0.328 Inches  Style Designator: Radial terminal each end  Test Data Document: 81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-26/3b government specification Shelf Life: N/a Unit Of Measure:	Terminal Type:
Note established  Terminal Length:  0.688 inches  Body Diameter:  1.312 inches  Body Length:  10.500 inches  Power Dissipation Rating In Watts:  210.000 free air  Terminal Width:  0.328 inches  Style Designator: Radial terminal each end  Test Data Document:  81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-26/3b government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Tab, solder lug
Terminal Length:  0.688 inches  Body Diameter:  1.312 inches  Body Length:  10.500 inches  Power Dissipation Rating In Watts:  210.000 free air  Terminal Width:  0.328 inches  Style Designator:  Radial terminal each end  Test Data Document:  81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-26/3b government specification  Shelf Life:  N/a  Unit Of Measure:	Reliability Indicator:
Body Diameter:  1.312 inches  Body Length:  10.500 inches  Power Dissipation Rating In Watts:  210.000 free air  Terminal Width:  0.328 inches  Style Designator:  Radial terminal each end  Test Data Document:  81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-26/3b government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Not established
Body Diameter:  1.312 inches  Body Length:  10.500 inches  Power Dissipation Rating In Watts:  210.000 free air  Terminal Width:  0.328 inches  Style Designator:  Radial terminal each end  Test Data Document:  81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-26/3b government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Terminal Length:
1.312 inches  Body Length: 10.500 inches  Power Dissipation Rating In Watts: 210.000 free air  Terminal Width: 0.328 inches  Style Designator: Radial terminal each end  Test Data Document: 81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-26/3b government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization:	0.688 inches
Body Length:  10.500 inches  Power Dissipation Rating In Watts:  210.000 free air  Terminal Width:  0.328 inches  Style Designator: Radial terminal each end  Test Data Document:  81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-26/3b government specification  Shelf Life: N/a  Unit Of Measure:   Demilitarization:	Body Diameter:
10.500 inches  Power Dissipation Rating In Watts: 210.000 free air  Terminal Width: 0.328 inches  Style Designator: Radial terminal each end  Test Data Document: 81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-26/3b government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization:	1.312 inches
Power Dissipation Rating In Watts:  210.000 free air  Terminal Width: 0.328 inches  Style Designator:  Radial terminal each end  Test Data Document:  81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-26/3b government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Body Length:
210.000 free air  Terminal Width: 0.328 inches  Style Designator: Radial terminal each end  Test Data Document: 81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-26/3b government specification  Shelf Life: N/a  Unit Of Measure: Demilitarization:	10.500 inches
Terminal Width:  0.328 inches  Style Designator:  Radial terminal each end  Test Data Document:  81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-26/3b government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Power Dissipation Rating In Watts:
O.328 inches  Style Designator:  Radial terminal each end  Test Data Document:  81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-26/3b government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	210.000 free air
Style Designator: Radial terminal each end  Test Data Document: 81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-26/3b government specification  Shelf Life: N/a Unit Of Measure: Demilitarization:	Terminal Width:
Radial terminal each end  Test Data Document:  81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-26/3b government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization:	0.328 inches
Test Data Document:  81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-26/3b government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Style Designator:
81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-26/3b government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Radial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-26/3b government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-26/3b government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	81349-mil-r-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal
Specification Data: 81349-mil-r-26/3b government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
81349-mil-r-26/3b government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:  N/a Unit Of Measure: Demilitarization:	Specification Data:
N/a Unit Of Measure: Demilitarization:	81349-mil-r-26/3b government specification
Unit Of Measure: Demilitarization:	Shelf Life:
Demilitarization:	N/a
	Unit Of Measure:
	<del></del>
NI_	Demilitarization:
NO NO	No