Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-755-8446

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Body Diameter:**

1.812 inches

#### Shaft Diameter:

0.250 inches

Shaft Length:

0.812 inches

Mounting Bushing Length:

#### 0.375 inches

Body Length:

#### 1.141 inches

Shaft Style:

Round

### Actuator Type:

Single shaft

### Nonturn Device Location:

At 6 oclock

#### Nonturn Device Radius:

0.562 inches

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

### **Mounting Method:**

Standard bushing

## **Electrical Resistance Per Section:**

1.000 kilohms single section

## Power Dissipation Rating Per Section In Watts:

3.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

# Standard Taper Curve Per Section:

A single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0