Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-758-1100

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

1.166 inches

#### Body Diameter:

1.156 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.531 inches

## Mounting Bushing Length:

## 0.375 inches

**Body Length:** 

0.625 inches

## **Overall Diameter:**

1.344 inches

## Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

300.0

## **Nonturn Device Location:**

At 9 oclock

## Nonturn Device Radius:

0.531 inches

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

1.000 kilohms single section

# NSN 5905-00-758-1100

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



**Rotary Actuator Travel In Angular Deg:** 300.0 **Function Conformity Tolerance Per Section:** -2.00/+2.00 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0