## NSN 5905-00-758-4698

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-758-4698 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.470 inches **Body Diameter:** 1.250 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.720 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.750 inches **Overall Diameter:** 1.850 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 340.0 **Maximum Starting Torque:** 4.00 inch-ounces **Maximum Stop Torque:** 150.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.531 inches **Shaft End Play:** 0.00500 inches **Shaft Runout:** 

Lateral Runout: 0.005 inches

0.002 inches

## NSN 5905-00-758-4698

Precision Wire Wound Variable Resistor - Page 2 of 3



Pilot Diameter Runout:
0.00200 inches
Shaft Radial Play:
0.004 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
98.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
350.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-2.0/+2.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section equation
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Special Features:
Removable stop location
Test Data Document:
12464-b75f0057 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:

No

## NSN 5905-00-758-4698

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0