## NSN 5905-00-758-4749

**Section Quantity:** 

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-758-4749

1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Overall Length:
0.690 inches
Terminal Length:
0.300 inches
Overall Height:
0.415 inches
Overall Width:
0.145 inches
Mounting Hole Diameter:
0.074 inches
Shaft Diameter:
0.060 inches
Shaft Length:
0.040 inches
Body Length:
0.390 inches
Body Width:
0.145 inches
Body Height:
0.375 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
0.10 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Lateral Distance Between Mounting Hole Centers:
0.419 inches
Mounting Facility Quantity:

## NSN 5905-00-758-4749

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
All adjacent sides from adjacent control
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
25.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0