

View Online at <https://aerobasegroup.com/nsn/5905-00-758-7630>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

1.3120 inches

**Pilot Length:**

0.0620 inches

**Undercut Diameter:**

1.312 inches

**Undercut Width:**

0.0630 inches

**Body Diameter:**

1.500 inches

**Shaft Diameter:**

0.187 inches

**Shaft Length:**

0.625 inches

**Body Length:**

0.750 inches

**Mounting Lip Diameter:**

1.5000 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

360.0

**Maximum Starting Torque:**

0.35 inch-ounces

**Maximum Running Torque:**

0.35 inch-ounces

**Shaft Radial Play:**

0.001 inches

**Screw Thread Diameter:**

0.112 inches

**Screw Thread Series Designator:**

Unc

**Screw Thready Qty Per Inch (tpi):**

28.0

**Mounting Facility Quantity:**

4

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Threaded hole

**Electrical Resistance Per Section:**

3.600 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.50/+0.50 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

Single section linear

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0