Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-759-3536

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Overall Length:

1.300 inches

Overall Height:

0.344 inches

Overall Width:

Between 0.283 inches and 0.297 inches

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.125 inches

Shaft Length:

Between 0.040 inches and 0.060 inches

Body Length:

1.250 inches

Body Width:

Between 0.283 inches and 0.297 inches

Body Height:

0.344 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

8640.0

Maximum Starting Torque:

8.00 inch-ounces

Shaft End Play:

0.00020 inches

Fragility Factor:

Moderately delicate

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

NSN 5905-00-759-3536

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
200.0 ohms single section
Rotary Actuator Travel In Angular Deg:
9720.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-0.0 to 250.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0