## NSN 5905-00-759-7303

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-759-7303 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.6240 inches and 0.6250 inches Pilot Length: Between 0.0570 inches and 0.0670 inches **Overall Length:** 2.362 inches **Undercut Diameter:** Between 0.745 inches and 0.755 inches **Undercut Width:** Between 0.0570 inches and 0.0670 inches **Body Diameter:** Between 0.850 inches and 0.890 inches **Shaft Diameter:** Between 0.124 inches and 0.125 inches **Shaft Length:** Between 0.531 inches and 0.593 inches **Body Length:** 1800.000 inches **Overall Diameter:** 0.995 inches **Mounting Lip Diameter:** Between 0.8500 inches and 0.8900 inches **Mounting Lip Depth:** Between 0.0570 inches and 0.0670 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 

3600.0 **Maximum Starting Torque:** 1.50 inch-ounces **Maximum Stop Torque:** 

80.00 inch-ounces

## NSN 5905-00-759-7303

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Fragility Factor:
Moderately rugged
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
5.0 ohms single section
Rotary Actuator Travel In Angular Deg:
3700.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-40.0/+40.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0