NSN 5905-00-759-8776

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-759-8776

25.0/+25.0 Electrical Resistance: 21.500 kilohms Resistance Tolerance in Percent: 40.500/+0.500 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/
Resistance Tolerance In Percent: -0.500/+0.500 Ambient Tempurature In Deg Celsius At Full Rated Power: -125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type:
Resistance Tolerance In Percent: -0.500/+0.500 Ambient Tempurature In Deg Celsius At Full Rated Power: -125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: -0.001 Body Diameter: -0.109 inches Body Length: -0.250 inches Power Dissipation Rating In Watts: -0.100 free air Style Designator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 10.001 Body Diameter: 10.109 inches Body Length: 10.250 inches Power Dissipation Rating In Watts: 10.100 free air Style Designator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
Power Dissipation Rating In Watts: 0.100 free air Style Designator:
0.100 free air Style Designator:
Style Designator:
Axial terminal each end
Test Data Document:
81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0