

View Online at <https://aerobasegroup.com/nsn/5905-00-761-1360>

**Section Quantity:**

1

**Body Style:**

Rectangular w/tab/flange mounted

**Reliability Indicator:**

Not established

**Thread Length:**

0.875 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

1.000 inches

**Body Length:**

2.500 inches

**Body Width:**

0.500 inches

**Body Height:**

0.625 inches

**Shaft Style:**

Round, threaded

**Shaft Bearing Type:**

Bearing

**Actuator Type:**

Single shaft

**Longitudinal Actuator Travel:**

1.31 inches

**Longitudinal Actuator Effective Electrical Stroke Length:**

0.725 inches

**Distance Between Mounting Hole Centers:**

0.344 inches

**Lateral Distance Between Mounting Hole Centers:**

2.650 inches

**Screw Thread Diameter:**

0.112 inches

**Screw Thread Series Designator:**

Unc

**Screw Thready Qty Per Inch (tpi):**

40.0

**Mounting Facility Quantity:**

4

**Terminal Location:**

Upper adjacent side single row

**Mounting Method:**

Threaded hole

**Electrical Resistance Per Section:**

10.000 kilohms single section

**Function Conformity Tolerance Per Section:**

-0.75/+0.75 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

200.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.4 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Special Features:**

Shaft has screw driver slot

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0