NSN 5905-00-761-3304

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-761-3304

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Overall Length:
0.750 inches
Terminal Length:
0.500 inches
Overall Height:
Between 0.245 inches and 0.255 inches
Overall Width:
Between 0.345 inches and 0.355 inches
Body Length:
Between 0.245 inches and 0.255 inches
Body Width:
Between 0.345 inches and 0.355 inches
Body Height:
Between 0.245 inches and 0.255 inches
Actuator Type:
Flush drive with slot-hole
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
All adjacent sides from adjacent control
Mounting Method:
Terminal
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.095 inches and 0.105 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:

Stops

NSN 5905-00-761-3304

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Ce	Isius:
--	--------

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0