NSN 5905-00-761-4399

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-761-4399 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.785 inches **Body Length:** 0.422 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 240.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Tab **Electrical Resistance Per Section:** 150.000 ohms single section **Rotary Actuator Travel In Angular Deg:** 240.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 1.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Continuous motion Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0 to 20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a

--

Unit Of Measure:

NSN 5905-00-761-4399

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0