## NSN 5905-00-761-4473

**Section Quantity:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-761-4473

Body Style:
Cylindrical bushing mounted
Overall Length:
1.938 inches
Body Diameter:
0.500 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.500 inches
Overall Diameter:
0.875 inches
Shaft Style:
Round
Switch Type:
Push-pull
Switch Voltage Rating In Volts:
125.0
Actuator Type:
Single shaft
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Double pole, double throw
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unc
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
50.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
290.0

## NSN 5905-00-761-4473

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:	
0.5 free air single section	
Resistance Tolerance Per Section In Percent:	
-20.0 to 20.0 single section	
Actuator Travel Control Feature:	
Continuous motion	
Switch Current Type And Rating In Amps:	
0.500 ac	
Standard Taper Curve Per Section:	
A single section	
Special Features:	
0.128 in. Diameter hole on center length of shaft, one 4-48 tapped hole through diameter of shaft	
Terminal Type And Quantity:	
3 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
<del></del>	
Demilitarization:	
No	
Fiig:	
A002a0	