NSN 5905-00-761-4600

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-761-4600 **Section Quantity:** 1 **Body Style:** Rectangular w/bushing/hole mounting **Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.074 inches **Shaft Diameter:** 0.190 inches **Shaft Length:** 0.250 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.375 inches **Body Width:** 0.203 inches **Body Height:** 0.375 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Screw Thread Diameter:** 0.190 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Standard bushing and unthreaded hole **Electrical Resistance Per Section:**

200.000 ohms single section **Rotary Actuator Travel In Angular Deg:**

9000.0

NSN 5905-00-761-4600

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:**