NSN 5905-00-761-5390

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-761-5390 **Section Quantity:** 2 **Body Style:** Rectangular w/bushing **Reliability Indicator:** Not established **Overall Length:** 2.156 inches **Overall Height:** 1.750 inches **Overall Width:** 1.234 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.406 inches **Body Width:** 1.234 inches **Body Height:** 1.438 inches **Shaft Style:** Round Switch Type: Pull **Switch Voltage Rating In Volts:** 117.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 312.0 **Nonturn Device Location:**

At 9 oclock **Nonturn Device Radius:**

0.531 inches

Switch Operating Position:

Any position of rotation travel

Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

NSN 5905-00-761-5390

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom Control of the Control o
Mounting Method:
Standard bushing
Features Provided:
Shaft seal and switch
Electrical Resistance Per Section:
1.0 kilohms 1st section and 100.0 kilohms 2nd section
Rotary Actuator Travel In Angular Deg:
312.0
Resistance Tempurature Characteristic Range Per Section In Percent:
-3.0 to 0.0 -55 degrees celsius all sections and -5.0 to 10.0 -25 degrees celsius all sections and -5.0 to 10.0 25 degrees celsius all sections
and +0.0 to 3.0 120 degrees celsius all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 all sections
Power Dissipation Rating Per Section In Watts:
1.0 free air 1st section and 2.0 free air 2nd section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Switch Current Type And Rating In Amps:
3.000 ac/dc
Standard Taper Curve Per Section:
C 1st section and a 2nd section
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No