Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-761-5884

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

### **Overall Length:**

1.876 inches

#### **Body Diameter:**

1.047 inches

### Shaft Diameter:

0.125 inches

### Shaft Length:

0.625 inches

### Mounting Bushing Length:

# 0.250 inches

**Body Length:** 

1.063 inches

### **Overall Diameter:**

1.047 inches

# Shaft Style:

Round, slotted

### **Contact Arm Electrical Off Position:**

Fully cw

### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

300.0

### Maximum Starting Torque:

6.00 inch-ounces

### Maximum Running Torque:

0.50 inch-ounces

### Maximum Stop Torque:

80.00 inch-ounces

### Nonturn Device Location:

At 6 oclock

# Nonturn Device Radius:

0.250 inches

### Screw Thread Diameter:

0.250 inches

### Screw Thread Series Designator:

Unef

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Rear end

Mounting Method:

Standard bushing

**Electrical Resistance Per Section:** 

1.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

300.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

Power Dissipation Rating Per Section In Watts:

6.25 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

### **Test Data Document:**

81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

3 tab, solder lug

**Specification Data:** 

81349-mil-r-22/2 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0