NSN 5905-00-761-6934

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-761-6934

Electrical Resistance: 0.000 ohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 850.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 85.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: 8004 Diameter: 9.093 inches 98040 Length: 9.343 inches Power Dissipation Rating In Watts: 9.550 free air Style Designator: xixial terminal each end Feet Daucement:
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 156.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 156.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 157.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 158.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 159.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/-125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Range Of Tempurature Range Of Tempurature Range O
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Tempurature Range Of Tempurature Range Of Tempurature Range Of Tempurature Range Of Tempur
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0. Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0. Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Rot established Rody Diameter: 20.093 inches Rody Length: 20.343 inches Power Dissipation Rating In Watts: 25.00 free air Style Designator: 25.01 kxial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 20.093 inches Body Length: 20.343 inches Power Dissipation Rating In Watts: 25.00 free air Style Designator: 25.01 inclosure Method: 25.02 inclosure Method: 25.03 inches 25.04 inches 25.04 inches 25.05 inches 2
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Inclosure Method: Tempurature Method: Tempuratur
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Inclosure Method: Incapsulated Terminal Type: Vire lead Reliability Indicator: And established Body Diameter: 1.093 inches Body Length: 1.343 inches Power Dissipation Rating In Watts: 1.550 free air Style Designator: xixial terminal each end Test Data Document:
Section 1950.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Inclosure Method: Inclosure Method:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.093 inches Body Length: 10.343 inches Power Dissipation Rating In Watts: 10.500 free air Style Designator: Axial terminal each end Fest Data Document:
inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established R
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: D.093 inches Body Length: D.343 inches Power Dissipation Rating In Watts: D.500 free air Style Designator: Axial terminal each end Fest Data Document:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.343 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Fest Data Document:
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.343 inches Power Dissipation Rating In Watts: 0.500 free air Reliability Designator: Axial terminal each end Fest Data Document:
Wire lead Reliability Indicator: Not established Rody Diameter: 0.093 inches Rody Length: 0.343 inches Power Dissipation Rating In Watts: 0.500 free air Ryle Designator: Axial terminal each end Fest Data Document:
Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.343 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Fest Data Document:
Not established Body Diameter: 0.093 inches Body Length: 0.343 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Fest Data Document:
Body Diameter: 0.093 inches Body Length: 0.343 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Fest Data Document:
2.093 inches Body Length: 2.343 inches Power Dissipation Rating In Watts: 2.500 free air Style Designator: Axial terminal each end Fest Data Document:
Body Length: 0.343 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document:
2.343 inches Power Dissipation Rating In Watts: 2.500 free air Style Designator: Axial terminal each end Test Data Document:
Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document:
0.500 free air Style Designator: Axial terminal each end Test Data Document:
Style Designator: Axial terminal each end Test Data Document:
Axial terminal each end Test Data Document:
Test Data Document:
0500 7000704 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
00536-7900784 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No.
Filig:
A001a0