

View Online at https://aerobasegroup.com/nsn/5905-00-761-7586

Section Quantity:

13

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

9.740 inches

Body Diameter:

1.750 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.500 inches

Mounting Bushing Length:

0.375 inches

Body Length:

8.240 inches

Overall Diameter:

2.000 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

280.0

Maximum Starting Torque:

3.00 inch-ounces

Maximum Running Torque:

2.00 inch-ounces

Maximum Stop Torque:

48.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef



Precision Wire Wound Variable Resistor - Page 2 of 2 Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference Mounting Method: Standard bushing **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 2.500 kilohms all sections **Rotary Actuator Travel In Angular Deg:** 280.0 **Function Conformity Tolerance Per Section:** -1.00/+1.00 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 all sections **Power Dissipation Rating Per Section In Watts:** 3.0 free air all sections **Function Conformity Per Section:** All sections independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 all sections **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections **Terminal Type And Quantity:** 39 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:** Fiig: A002a0

No