

View Online at <https://aerobasegroup.com/nsn/5905-00-761-7587>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

3.085 inches

Body Diameter:

1.750 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.500 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.585 inches

Overall Diameter:

2.000 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

280.0

Maximum Starting Torque:

2.00 inch-ounces

Maximum Running Torque:

1.50 inch-ounces

Maximum Stop Torque:

128.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Electrical Resistance Per Section:

1.250 kilohms all sections

Rotary Actuator Travel In Angular Deg:

280.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 all sections

Power Dissipation Rating Per Section In Watts:

3.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

All sections linear

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0