

View Online at <https://aerobasegroup.com/nsn/5905-00-762-2575>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.656 inches

First Flat Length:

0.250 inches

Flat Height:

0.185 inches

Body Diameter:

1.156 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.718 inches

Mounting Bushing Length:

0.406 inches

Body Length:

0.750 inches

Overall Diameter:

1.484 inches

Shaft Style:

Round, parallel flatted

Switch Type:

Rotary

Switch Voltage Rating In Volts:

125.0

Contact Arm Electrical Off Position:

Fully ccw

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

330.0

Maximum Stop Torque:

128.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Single pole, single throw, normally closed

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear-bottom

Mounting Method:

Standard bushing

Features Provided:

Switch

Electrical Resistance Per Section:

50.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

340.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Switch Current Type And Rating In Amps:

2.000 ac/dc

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0