## NSN 5905-00-762-2575

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-762-2575 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.656 inches First Flat Length: 0.250 inches Flat Height: 0.185 inches **Body Diameter:** 1.156 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.718 inches **Mounting Bushing Length:** 0.406 inches **Body Length:** 0.750 inches **Overall Diameter:** 1.484 inches **Shaft Style:** Round, parallel flatted Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Contact Arm Electrical Off Position:** Fully ccw **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 330.0 **Maximum Stop Torque:** 128.00 inch-ounces **Nonturn Device Location:** 

At 9 oclock **Nonturn Device Radius:** 

0.531 inches

## NSN 5905-00-762-2575

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally closed
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
340.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
2.000 ac/dc
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

No

## NSN 5905-00-762-2575

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0