Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-00-763-2513

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Overall Length:** 1.300 inches **Overall Height:** Between 0.290 inches and 0.310 inches **Overall Width:** Between 0.170 inches and 0.190 inches Mounting Hole Diameter: 0.086 inches Shaft Diameter: Between 0.040 inches and 0.060 inches Shaft Length: Between 0.110 inches and 0.130 inches **Body Length:** Between 1.240 inches and 1.260 inches **Body Width:** Between 0.170 inches and 0.190 inches **Body Height:** Between 0.290 inches and 0.310 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 8.00 inch-ounces Lateral Distance Between Mounting Hole Centers: Between 0.995 inches and 1.005 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 500.000 ohms single section **Rotary Actuator Travel In Angular Deg:** 7920.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0 to 70.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0