Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AGIU

View Online at https://aerobasegroup.com/nsn/5905-00-763-2515

Section Quantity: 1 Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Overall Length:

1.470 inches

Overall Height:

Between 0.290 inches and 0.310 inches

Overall Width:

Between 0.170 inches and 0.190 inches

Mounting Hole Diameter:

0.086 inches

Shaft Diameter:

Between 0.110 inches and 0.130 inches

Shaft Length:

Between 0.040 inches and 0.060 inches

Body Length:

Between 1.240 inches and 1.260 inches

Body Width:

Between 0.170 inches and 0.190 inches

Body Height:

Between 0.290 inches and 0.310 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

8.00 inch-ounces

Lateral Distance Between Mounting Hole Centers:

Between 0.995 inches and 1.005 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

10.000 ohms single section

Rotary Actuator Travel In Angular Deg:

7920.0



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0 to 70.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire loop Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0