NSN 5905-00-763-2516

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-763-2516

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
Between 1.280 inches and 1.320 inches
Overall Height:
Between 0.290 inches and 0.310 inches
Overall Width:
Between 0.170 inches and 0.190 inches
Mounting Hole Diameter:
0.086 inches
Shaft Diameter:
Between 0.110 inches and 0.130 inches
Shaft Length:
Between 0.040 inches and 0.060 inches
Body Length:
Between 1.240 inches and 1.260 inches
Body Width:
Between 0.170 inches and 0.190 inches
Body Height:
Between 0.290 inches and 0.310 inches
Shaft Style:
Round, slotted
Contact Arm Electrical Off Position:
Fully cw
Actuator Type:
Single shaft
Maximum Starting Torque:
5.00 inch-ounces
Lateral Distance Between Mounting Hole Centers:
Between 0.995 inches and 1.005 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:

10.000 kilohms single section

NSN 5905-00-763-2516

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg: Between 8698.0 and 8702.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -70.0 to 70.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire loop Shelf Life: N/a **Unit Of Measure:** Demilitarization: