

View Online at <https://aerobasegroup.com/nsn/5905-00-763-2516>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Overall Length:

Between 1.280 inches and 1.320 inches

Overall Height:

Between 0.290 inches and 0.310 inches

Overall Width:

Between 0.170 inches and 0.190 inches

Mounting Hole Diameter:

0.086 inches

Shaft Diameter:

Between 0.110 inches and 0.130 inches

Shaft Length:

Between 0.040 inches and 0.060 inches

Body Length:

Between 1.240 inches and 1.260 inches

Body Width:

Between 0.170 inches and 0.190 inches

Body Height:

Between 0.290 inches and 0.310 inches

Shaft Style:

Round, slotted

Contact Arm Electrical Off Position:

Fully cw

Actuator Type:

Single shaft

Maximum Starting Torque:

5.00 inch-ounces

Lateral Distance Between Mounting Hole Centers:

Between 0.995 inches and 1.005 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

10.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 8698.0 and 8702.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0 to 70.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire loop

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0