

View Online at <https://aerobasegroup.com/nsn/5905-00-763-2522>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

2.766 inches

**Flat Height:**

Between 0.094 inches and 0.216 inches

**Body Diameter:**

1.156 inches

**Shaft Diameter:**

Between 0.125 inches and 0.250 inches

**Shaft Length:**

Between 1.100 inches and 1.500 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

1.266 inches

**Overall Diameter:**

1.156 inches

**Undercut Diameter:**

0.063 inches

**Shaft Style:**

Round, stepped

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.531 inches

**Fragility Factor:**

Moderately rugged

**Undercut Length:**

0.550 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

10.0 kilohms 1st section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 all sections

**Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 all sections

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 all sections

**Standard Taper Curve Per Section:**

A all sections

**Test Data Document:**

95542-138-063 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0