NSN 5905-00-763-5372

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



Section Quantity:	
1	
Body Style:	
Rectangular w/mounting holes/sl	ots
Reliability Indicator:	
Not established	
Terminal Length:	
Between 0.285 inches and 0.315	inches
Mounting Hole Diameter:	
0.074 inches	
Shaft Diameter:	
Between 0.080 inches and 0.100	inches
Shaft Length:	
Between 0.030 inches and 0.050	inches
Body Length:	
Between 0.365 inches and 0.385	inches
Body Width:	
Between 0.188 inches and 0.219	inches
Body Height:	
Between 0.365 inches and 0.385	inches
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Center To Center Distance Bet	veen Terminals:
0.200 inches	
Lateral Distance Between Mou	nting Hole Centers:
0.406 inches	
Mounting Facility Quantity:	
1	

Left adjacent side two rows

Mounting Method:

Terminal and unthreaded hole

Center To Center Distance Between Terminal Rows:

0.100 inches

Electrical Resistance Per Section:

5.000 kilohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.090 inches and 0.110 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

NSN 5905-00-763-5372

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0