NSN 5905-00-763-5377

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-763-5377 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting hole/slot **Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.074 inches **Shaft Diameter:** Between 0.080 inches and 0.100 inches **Shaft Length:** Between 0.030 inches and 0.050 inches **Body Length:** Between 0.360 inches and 0.390 inches **Body Width:** Between 0.187 inches and 0.219 inches **Body Height:** Between 0.360 inches and 0.390 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Nonturn Device Location:** At 2 oclock **Nonturn Device Radius:** 0.188 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 100.000 ohms single section **Rotary Actuator Travel In Angular Deg:** 9000.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

NSN 5905-00-763-5377

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** One 0.074 in diameter mtg hole centrally located **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:** No