

View Online at <https://aerobasegroup.com/nsn/5905-00-763-5377>

**Section Quantity:**

1

**Body Style:**

Rectangular w/mounting hole/slot

**Reliability Indicator:**

Not established

**Mounting Hole Diameter:**

0.074 inches

**Shaft Diameter:**

Between 0.080 inches and 0.100 inches

**Shaft Length:**

Between 0.030 inches and 0.050 inches

**Body Length:**

Between 0.360 inches and 0.390 inches

**Body Width:**

Between 0.187 inches and 0.219 inches

**Body Height:**

Between 0.360 inches and 0.390 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

9000.0

**Nonturn Device Location:**

At 2 oclock

**Nonturn Device Radius:**

0.188 inches

**Mounting Facility Quantity:**

1

**Terminal Location:**

Rear end

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

100.000 ohms single section

**Rotary Actuator Travel In Angular Deg:**

9000.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

175.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-50.0 to 50.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Special Features:**

One 0.074 in diameter mtg hole centrally located

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0