## NSN 5905-00-763-5634

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-763-5634 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.9683 inches and 0.9688 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 0.975 inches **Undercut Width:** 0.0570 inches **Body Diameter:** 1.125 inches **Shaft Diameter:** Between 0.1245 inches and 0.125 inches **Shaft Length:** 0.625 inches **Body Length:** 0.810 inches **Mounting Lip Diameter:** 1.0620 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 0.40 inch-ounces **Shaft End Play:** 

0.005 inches **Shaft Runout:** 0.001 inches

## NSN 5905-00-763-5634

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Lateral Runout:	
0.001 inches	
Pilot Diameter Runout:	
0.001 inches	
Shaft Radial Play:	
0.001 inches	
Mechanical Backlash In Deg Angular Rotation:	
0.25	
Fragility Factor:	
Rugged	
Terminal Location:	
Radially positioned over more than half the circumference	
Mounting Method:	
Clamp ring	
Electrical Resistance Per Section:	
2.0 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
360.0	
Function Conformity Tolerance Per Section:	
0.50 to 0.50 single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
125.0 single section	
Power Dissipation Rating Per Section In Watts:	
1.25 free air single section	
Function Conformity Per Section:	
Single section absolute conformity	
Resistance Tolerance Per Section In Percent:	
10.0 to 10.0 single section	
Actuator Travel Control Feature:	
Continuous motion	
Function Characteristic Per Section:	
Single section 360 degrees sine-cosine	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Unpackaged Unit Weight:	
1.25 ounces	
Test Data Document:	
00752-373734 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;	
excludes any specification, standard or other document that may be referenced in a basic governing drawing)	
Terminal Type And Quantity:	
6 turret	
Shelf Life:	
N/a	
Unit Of Measure:	

## NSN 5905-00-763-5634

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0