## NSN 5905-00-763-8281

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-763-8281

View Online at https://aerobasegroup.com/nsn/5905-00-763-
Section Quantity:
1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Overall Length:
Between 0.515 inches and 0.555 inches
Terminal Length:
6.000 inches
Overall Height:
Between 0.490 inches and 0.510 inches
Overall Width:
Between 0.182 inches and 0.197 inches
Mounting Hole Diameter:
Between 0.090 inches and 0.098 inches
Shaft Diameter:
Between 0.058 inches and 0.098 inches
Shaft Length:
Between 0.025 inches and 0.045 inches
Body Length:
Between 0.490 inches and 0.510 inches
Body Width:
Between 0.182 inches and 0.197 inches
Body Height:
Between 0.490 inches and 0.510 inches
Shaft Style:
Round, slotted
Contact Arm Electrical Off Position:
Fully cw
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 7200.0 and 16200.0
Maximum Starting Torque:
8.00 inch-ounces
Lateral Distance Between Mounting Hole Centers:
Between 0.513 inches and 0.526 inches
Mounting Facility Quantity:
2

**Terminal Location:** 

Rear end

## NSN 5905-00-763-8281

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:	
Unthreaded hole	
Electrical Resistance Per Section:	
100.000 ohms single section	
Rotary Actuator Travel In Angular Deg:	
Between 7200.0 and 16200.0	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
150.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
-50.0 to 50.0 single section	
Power Dissipation Rating Per Section In Watts:	
0.75 free air single section	
Resistance Tolerance Per Section In Percent:	
-5.0 to 5.0 single section	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
85.0 single section	
Standard Taper Curve Per Section:	
A single section	
Test Data Document:	
81349-mil-r-27208 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	ation
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Terminal Type And Quantity:	
3 wire lead	
Specification Data:	
81349-mil-r-27208/4 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	