NSN 5905-00-763-8839

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-763-8839 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** Between 0.609 inches and 0.641 inches **Shaft Diameter:** Between 0.155 inches and 0.157 inches **Shaft Length:** 0.125 inches **Body Length:** Between 0.344 inches and 0.375 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.125 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing and tab **Electrical Resistance Per Section:** 50.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -30.0/+30.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5905-00-763-8839

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0