NSN 5905-00-763-9194



Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-00-763-9194 **Section Quantity: Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.300 inches **Overall Height:** Between 0.328 inches and 0.360 inches **Overall Width:**

Between 0.283 inches and 0.297 inches

Mounting Hole Diameter:

Between 0.088 inches and 0.098 inches

Shaft Diameter:

Between 0.120 inches and 1.130 inches

Shaft Length:

Between 0.040 inches and 0.060 inches

Body Length:

Between 1.134 inches and 1.266 inches

Body Width:

Between 0.283 inches and 0.297 inches

Body Height:

Between 0.328 inches and 0.360 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

8640.0

Maximum Starting Torque:

8.00 inch-ounces

Shaft End Play:

0.00020 inches

Lateral Distance Between Mounting Hole Centers:

Between 0.950 inches and 1.005 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

NSN 5905-00-763-9194

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:	
500.000 ohms single section	
Rotary Actuator Travel In Angular Deg:	
9720.0	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
175.0 single section	
Power Dissipation Rating Per Section In Watts:	
1.0 free air single section	
Resistance Tolerance Per Section In Percent:	
10.0 to 10.0 single section	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
35.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 wire lead	
Shelf Life:	
N/a	
Unit Of Measure:	
.	
Demilitarization:	
No	
Filg:	
A002a0	