NSN 5905-00-764-0420

Section Quantity:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-764-0420

1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
Between 1.656 inches and 1.750 inches
Body Diameter:
Between 0.890 inches and 0.922 inches
Shaft Diameter:
Between 0.248 inches and 0.251 inches
Shaft Length:
Between 1.219 inches and 1.281 inches
Mounting Bushing Length:
0.375 inches
Body Length:
Between 0.437 inches and 0.469 inches
Overall Diameter:
1.274 inches
Shaft Style:
Shaft Style: Round, slotted
•
Round, slotted
Round, slotted Actuator Type:
Round, slotted Actuator Type: Single shaft
Round, slotted Actuator Type: Single shaft Maximum Starting Torque:
Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces
Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque:
Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces
Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location:
Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock
Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius:
Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.422 inches and 0.454 inches
Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.422 inches and 0.454 inches Fragility Factor:
Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.422 inches and 0.454 inches Fragility Factor: Moderately rugged
Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.422 inches and 0.454 inches Fragility Factor: Moderately rugged Screw Thread Diameter:
Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.422 inches and 0.454 inches Fragility Factor: Moderately rugged Screw Thread Diameter: 0.375 inches

Terminal Location:

32.0

Radially positioned over less than half the circumference

NSN 5905-00-764-0420

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Standard bushing
Electrical Resistance Per Section:
2.0 megohms single section
Rotary Actuator Travel In Angular Deg:
Between 251.0 and 318.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A002a0