## NSN 5905-00-764-0423

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-764-0423

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Overall Length:
1.359 inches
Terminal Length:
0.624 inches
Overall Height:
0.300 inches
Overall Width:
0.300 inches
Mounting Hole Diameter:
0.098 inches
Shaft Diameter:
0.140 inches
Shaft Length:
0.077 inches
Body Length:
1.282 inches
Body Width:
0.300 inches
Body Height:
0.300 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9720.0
Maximum Starting Torque:
8.00 inch-ounces
Center To Center Distance Between Terminals:
0.510 inches
Lateral Distance Between Mounting Hole Centers:
0.160 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side two rows
Mounting Method:

Unthreaded hole

## NSN 5905-00-764-0423

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Terminal Rows:
0.105 inches
Electrical Resistance Per Section:
00.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
0720.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.290 inches and 0.310 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
25.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
600.0 to 600.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
31349-milr22097-1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Ferminal Type And Quantity:
3 pin
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No.
Filg:
A002a0