Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-764-0426

Section Quantity: 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 1.201 inches and 1.273 inches **Body Diameter:** Between 0.859 inches and 0.891 inches Shaft Diameter: 0.125 inches Shaft Length: Between 0.265 inches and 0.359 inches Mounting Bushing Length: Between 0.296 inches and 0.328 inches **Body Length:** Between 0.547 inches and 0.551 inches **Overall Diameter:** Between 1.031 inches and 1.095 inches Shaft Style: Round **Contact Arm Electrical Off Position:** Fully ccw-cw Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: Between 1080.0 and 1090.0 **Maximum Starting Torque:** 0.60 inch-ounces Maximum Running Torque: 0.60 inch-ounces Maximum Stop Torque: 48.00 inch-ounces Shaft End Play: 0.005 inches Shaft Runout: 0.002 inches Shaft Radial Play: 0.002 inches **Screw Thread Diameter:** 0.250 inches

Precision Wire Wound Variable Resistor - Page 2 of 2



**Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 5.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 1080.0 and 1090.0 **Function Conformity Tolerance Per Section:** -0.30/+0.30 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0