Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-764-3956

Section Quantity:

2

Reliability Indicator:

Not established

Shaft Diameter:

0.250 inches

Shaft Length:

0.750 inches

Mounting Bushing Length:

0.375 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

500.000 kilohms 2nd section

Power Dissipation Rating Per Section In Watts:

2.25 free air 1st section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 2nd section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5905-00-764-3956

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

Fiig: A002a0

