Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-764-4865

Section	Quantity:

1

- Body Style: Rectangular w/mounting holes
- Reliability Indicator:
- Not established
- Terminal Length:
- 0.172 inches
- Mounting Hole Diameter:
- 0.073 inches
- Shaft Diameter:
- 0.093 inches
- Shaft Length:
- 0.075 inches
- Body Length:
- 0.375 inches
- **Body Width:**
- 0.185 inches
- Body Height:
- 0.405 inches
- Shaft Style:
- Round, slotted
- Actuator Type:
- Single shaft
- Effective Electrical Rotation In Deg Angular Rotation:
- 9000.0
- **Center To Center Distance Between Terminals:**
- 0.200 inches
- Lateral Distance Between Mounting Hole Centers:
- 0.375 inches
- Mounting Facility Quantity:
- 2
- **Terminal Location:**
- Lower adjacent side single row
- **Mounting Method:**
- Terminal and unthreaded hole
- **Electrical Resistance Per Section:**
- 500.000 ohms single section
- **Rotary Actuator Travel In Angular Deg:**
- 9000.0
- Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0